



ABEC BEARING SERIES LTD



0.787 Inch | 20 Millimeter x 1.72 Inch | 43.7
Millimeter x 1.311 Inch | 33.3 Millimeter TIMKEN
RAS 20 Pillow Block Bearings

Bearing No. RAS 20

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.64
EAN	0087796107892
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	10 Millimeter
Relubricatable	Yes
Insert Part Number	GE20KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Spherical Normal Duty High Base With Set Screw
Long Description	2 Bolt Pillow Block; 20MM Bore; 33.3MM Base to Center Height; Eccentric

RAS 20 Bearing 2D drawings and 3D CAD models



ABEC BEARING SERIES LTD

	Collar Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	RAS 20
Weight / LBS	1.4
Actual Bolt Center to Center	3.8 Inch 96Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
D	1.72 Inch 43.7 Millimeter
B	1.311 Inch 33.3 Millimeter
d	0.787 Inch 20 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Nominal Bolt Center to Center	3.8 Inch 97 Millimeter
Shaft Size d	0.787 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.657 in
Series	Industrial
Weight	1.609 lb
Seal Type	Shroud Seal
Base to Center Height H	33.34 mm
Total Length L	127.00 mm
Total Width A	1.311 in
Bolt Hole Spacing J	96.4 mm



ABEC BEARING SERIES LTD

Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	20.2 mm
Foot Height H1	15.1 mm
Total Height H2	65.9 mm
Dimension L1	42.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	17.1 mm
Dimension B1	1.72 in
Static Load Rating	1460 lbf
Dynamic Load Rating	3190 lbf